

Proton - R4320P

Industrial 4-port RAIN RFID Long Range Reader



Features

- RAIN RFID (UHF EPC Class1 Gen2, ISO 18000-63) compliant
- Multiregional support
- Four 50 Ohm TNC-RP antenna connectors
- Power over Ethernet interface
- Up to 31.5 dBm (1.4W) output power
- Internal scripting engine
- IP65 in compact form factor
- PoE or external power supply
- M12 industrial connectors
- Development Kit available

Applications

- RAIN RFID portals for logistic
- Industrial automation reading points
- RAIN RFID tunnels
- Access control reading points

Overview

The **Proton** (Model R4320P) is a rugged long range RAIN RFID reader of the easy2read® product line, well suited for industrial environment installations.

The **Proton** reader has 4 antenna ports capable of a 31.5 dBm maximum power enabling to build RAIN RFID portals for logistic. Its compact form factor makes it easy to install and the IP65 protection permits outdoor or harsh environment installations. Featuring Power Over Ethernet, RS232 and GPIOs via industry standard M12 connectors the **Proton** is an ideal choice for industrial automation and Industry 4.0 solutions.

The **Proton** is based upon an embedded Linux platform and it's easily configurable using an internal web interface. System integrators can customize the behavior of the reader installing Java code that, having access to all the RFID features and interfaces, permits a full customization.

The **Proton** reader complies with and can operate in both European and US regulatory environments and, due to its multiregional capabilities, it's ideal for integration in solutions requiring compliance to different geographical regions.

Technical Specification Table

Frequency Range	- 865.600÷867.600 MHz (ETSI EN 302 208 v. 3.1.1) - 902÷928 MHz (FCC part 15.247)
RF Power	- Up to 31.5 dBm (1.4W) conducted (ETSI) - Up to 30 dBm (1W) conducted (FCC)
Number of Channels	- 4 channels (compliant to ETSI EN 302 208 v. 3.1.1) - 50 hopping channels (compliant to FCC part 15.247)
Standard Compliance	EPC Class 1 Gen 2 - ISO18000-63
CPU	ARM9 @ 400MHz on Atmel AT91SAM9G25
Operating System	Linux
Receiving Capability	- Gen 2 Dense Reader Mode Management - Data rate up to 400kb/s
Connectivity	- RS232 Serial Communication (M12 connector) - Baudrate up to 115.200kbps - Databits: 8 - Stopbit: 1 - Parity: none - Flow control: none - Ethernet 10/100/1000Base-T (M12 connector) - PoE standard IEEE 802.3af
I/O Interface	- M12 connector - 2 digital inputs optically isolated - 2 solid state photorelay outputs optically isolated (500mA max)
Antenna Connectors	4 TNC Reverse Polarity
Power Supply	- 9÷36V DC power supply (12W) - PoE standard IEEE 802.3af (12.95W)
Status Indicators	Multicolour LEDs: Power, Activity, Status and Applications
IP Rating	IP 65
Dimensions	- (W)131 x (L)106 x (H)50 mm ³ - 5.15 x 4.17 x 1.96 inches ³
Operating Temperature	-10°C to +55°C
Weight	530 g.



Ordering Options

WR4320PXAAAA	Proton - Industrial Long Range Reader		
WR4320PXDKEU	Proton - ETSI Dev. Kit		
WR4320PXDKUS	Proton - FCC Dev. Kit		
WALIM0000006	Proton power supply - EU		
WALIM0000007	Proton power supply - US		